

# CABLE TO CABLE, TA, 250 KCMIL CONCENTRIC, 0.575" CONDUCTOR 1 OD, 4/0 CONCENTRIC, 0.528" CONDUCTOR 2 OD

#### **CATALOG NUMBER**

# TAC2V2Q



### **FEATURES**

Forms a permanent, low resistance connection

Provides a molecular bond

nVent ERICO Cadweld Exothermic Connections are rated with the same current capacity as the conductor

Portable installation equipment with no external source of power required

Installers can be easily trained to make nVent ERICO Cadweld Exothermic Connections

Connections can be visually inspected

#### PRODUCT ATTRIBUTES

Article Number: 240157

Mold Family: TA

Conductor 1: 250 kcmil Concentric

Conductor 1 Outer Diameter, Nominal: 14.6 mm

Conductor 2: 4/0 Concentric

Conductor 2 Outer Diameter, Nominal: 13.4 mm

Split Crucible: No

Wear Plates: No

Mold Only: No

Welding Material: 150 or 150PLUSF20, Sold Separately

Handle Clamp: L160, Sold Separately

Price Key: C

#### ADDITIONAL PRODUCT DETAILS

nVent ERICO Cadweld graphite molds are designed and engineered for thousands of connection styles and conductor combinations.

For applications such as computer room, tunnel or other low-ventilation areas, specify a smokeless nVent ERICO Cadweld Exolon mold. Add an XL prefix to the standard mold part number when ordering (for example, a TAC2Q2Q becomes XLTAC2Q2Q). Similarly, nVent ERICO Cadweld Exolon welding material is also designated by the XL prefix (for example, 150 becomes XL150).

A gap between conductors may be required. See mold tag for more information.

#### **WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

## North America

+1.800.753.9221

Option 1 - Customer Care Option 2 - Technical Support Europe

Netherlands: +31 800-0200135

France:

+33 800 901 793

Europe

Germany: 800 1890272 Other Countries: +31 13 5835404 **APAC** 

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500

